




# 塔帽式塔式起重机 设备配置与技术参数

QTZ50 (5008)

本数据仅供参考，如有更改，恕不另行通知

This data is for informational purposes only, and is subject to change without prior notice


## 外形尺寸 Outline Dimensions



## 载荷特性表 Load Diagrams 4t

R(m)	Fall	R <sub>C(max)</sub> (m)	C <sub>max</sub> (t)	15	20	25	30	35	36.8	40	43.4	45	50
50m		13.1	4.0	3.48	2.51	1.91	1.53	1.26	1.23	1.05	0.95	0.87	0.77
		24.3	2.0	2.0	2.0	1.94	1.56	1.29	1.26	1.08	0.98	0.9	0.8
43.4m		13.8	4.0	3.87	2.67	1.97	1.64	1.35	1.25	1.14	1.01		
		25.7	2.0	2.0	2.0	2.0	1.67	1.38	1.28	1.17	1.04		
36.8m		13.8	4.0	3.87	2.67	1.97	1.64	1.35	1.25				
		25.7	2.0	2.0	2.0	2.0	1.67	1.38	1.28				


### 塔身截面 Masts



	●	■
F2	47.7t	57.9t
F3	32.5t	43.3t
	20.4t	

- 工作状态支反力 Reactions in service
- 非工作状态支反力 Reactions out of service
- 不含平衡重及压重塔机重量 Total weight of free standing crane (exclude Counter weight & ballast)

### 附着位置及塔机高度 Anchorage



## 机构 Mechanisms 4t

名称	机构代号	工作速度 (m/min)	起重量(t)	容绳量(m)	电机功率	
起升 Hoisting	15JLD10	双绳 2 fall	10	2.0	250 >250*	15/15/4
			35	2.0		
			70	0.8		
		四绳 4 fall	5	4.0		
			17.5	4.0		
			35	1.6		
变幅机构 Trolleying	BE2450	40/20			2.4/1.5	
回转机构 Slewing	HR.80.157	0~0.6			3.7	
电源 Power	380V ( ± 10% ) /50Hz*					

\*请与制造商联系 contact us please

## 平衡重 Counter weight

			PHZ2200	PHZ1150
50m	11.18m	8900	3	2
43.4m	11.18m	7750	3	1
36.8m	11.18m	6600	3	



## **山东大汉建设机械股份有限公司**

地址：山东省济南市章丘区明水经济开发区赭山工业园

电话：+86 ( 531 ) 83260789

网址：www.dhtj.com

邮编：250200

## **Shandong Dahan Construction Machinery Co.,Ltd.**

Add : Zheshan Industrial Part,Mingshui Development  
Zone,Zhangqiu,Jinan City,Shandong Province,China

TEL : +86 ( 531 ) 83260789

Web : [http:// www.dhtj.com](http://www.dhtj.com)

ZIP CODE : 250200